

HERMAwhite (601)

White, machine-finished label paper

Specifications

Grammage	approx. 70 g/m ²	ISO 536
Caliper	approx. 67 µm	ISO 534
Tensile strength MD	approx. 83 N/15 mm	DIN 53112
Tensile strength CD	approx. 43 N/15 mm	DIN 53112
Stiffness MD	approx. 150 mN	DIN 53121
Stiffness CD	approx. 77 mN	DIN 53121
Opacity	approx. 83 %	ISO 2471

Application and use

The machine-finished surface of the ecf bleached HERMAwhite offers an excellent quality of the imprint with all traditional printing methods. The material is equally suitable for thermo transfer printing and is thus universally applicable. It is also perfect for laser printers. The shelf life of following adhesive combinations 92C, 92K, 62K, 42N and 42R are restricted to one year after manufacturing.

Regulations concerning contact with food

This paper is approved according to the Deutsche Empfehlung BfR XXXVI. This paper grade according to the sample material submitted may be used safely for food packaging. It may stand in direct contact with dry and fatty foodstuffs. (ISEGA Research and Development Institute, Aschaffenburg).

All statements, technical information and recommendations regarding HERMA products are given in good faith and are based on tests that we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.